

ALL REGISTRATION MARK DETECTION APPLICATIONS



- Teach-in, Remote settings
- Red/green or white LED emission
- Various interchangeable lenses and fiber-optic models
- Metal housing with orientable optics and connector

Detection properties

Nominal sensing distance	22mm
Sensitivity adjustment	Teach-in

Application

Function Principle	Contrast mark detection
Description	Standard case - vertical spot
Optic position	axial
Functions	Contrast mark detection

Outputs

Output type	NPN/PNP push-pull
Response time	0,05 (10kHz)

Electrical data

Operating Voltage	10...30VDC
No-Load supply current	≤ 80mA
Output voltage drop	≤2V

LED indicators	red OUTPUT greenREADY
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED RGB
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 M Ω 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

Mechanical data

Dimensions	31x58x82
Housing Material	Metal - Zamak
Connections	M12 plug
Active Head Material	Glass
Storage temperature	- 20°C...+70°C
Material	
Diameter/Dimension	Cubic

Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	31x58x82
Operating Temperature	-10°C ... 55°C
Mechanical Protection	IP67

Datasensing S.r.l.

Strada S.Caterina, 235

41122 Modena (MO)

Tel. 059 420411

Fax 059 253973

E-mail info@datasensing.com

date of printing

01/03/2024 11:26:54