



## Detection properties

Nominal sensing distance	8000mm
Thermal drift of Sr	±5%
Repeat Accuracy	1% valore fondoscala
Beam angle	10° ± 2°
Resolution	1% valore fondoscala
Sensitivity adjustment	Teach-in button
Hysteresis	1% valore fondoscala
thermal compensation	Si
Minimum sensing distance (blind zone)	600mm
Linearity error	1% valore fondoscala

## Application

Function Principle: Diffuse reflection

## Outputs

Output type	PNP + 4...20mA
Output Function	NO/NC + positive/negative slope
Switching frequency	1Hz

Response time	1s
---------------	----

## Electrical data

Operating Voltage	10 - 30Vdc
No-Load supply current	25mA
Load current	100mA
Leakage current	≤ 10μA @ 30Vdc
Output voltage drop	2,2V max @ IL=100mA
Max ripple content	5%
LED indicators	Verde: Eco - Giallo: Uscita
Time delay before availability	≤400ms
Short-circuit protection	Sì
Reverse Polarity Protection	Sì
Impulsive Overvoltage Protection	Sì

## Mechanical data

Dimensions	ø 61mm / L = 115mm
Weight	400g
Housing Material	AISI316L
Connections	M12 Plug
Tightening torque	100Nm
Operating temperature	-20°C...+70°C
Storage temperature	-30°C...+80°C
Transducer Frequency	40KHz
Diameter/Dimension	M30

## Test/Approvals

Approvals	CE cULus
EMC compatibility	IEC 60947-5-2
Shocks and vibrations	IEC EN 60947-5-2 / 7.4
Degree of protection	IP67

## Accessories

Supplied Accessories	2 x M30x1,5 dadi
----------------------	------------------

**VoxinTech**

Email: [info@voxintech.com](mailto:info@voxintech.com)

Web: [www.voxintech.com](http://www.voxintech.com)